

memory maps

- auxiliary memory 87
- bank-switched areas 82
- double-high-resolution graphics 37
- 80-column text 34
- 40-column text 33, 177
- high-resolution graphics 36
- I/O 142
- low-resolution graphics 35
- main memory 75
- RAM 76

memory pages, reserved 77–81

microprocessor *See*

- 6502 microprocessor;
- 65C02 microprocessor

Mini-Assembler 123–126

errors 125

instruction formats 126

starting 123

MIXED soft switch 29

MMU 5, 6, 164–165

Monitor, System 100–129

command summary 127–129

command syntax 101

creating commands 119

firmware subroutines 46–71

returning to BASIC 115

ROM listings 307–347

use of page 3 8

use of page zero 79

Monitor ROM 168–169

listings 307–347

MouseText characters 17, 19, 246

MOVE command 107–108, 117

MOVE subroutine 223

MSLOT 150, 154

N

NAK character 54

negative decimal values 12

converting 239–240

NEXTCOL subroutine 223

9-pin connectors 8, 40

NORMAL command 270–271

normal format 19–20, 114

NTSC standard 16, 25, 173

O

Open Apple (C) 11, 13, 228

operating systems 233–234

original Apple IIe *See* differences
between original and enhanced
Apple IIe

output *See* I/O

overheating 158

P

Page 1

double-high-resolution 79

high-resolution 23, 27, 79

text 27, 78

Page 2

high-resolution 23, 79

text 27, 79

page 3 vectors 97

page zero 77, 79–81

PAGE2 soft switch 29, 32, 87, 89,
90

pages, reserved memory 77–81

PAL device 5, 167–168

parity for SSC 279

Pascal xx, 235, 275

and bank-switched memory 82

I/O subroutines 46

starting up with 267–268

Pascal 1.1 firmware protocol 68–71,
144, 145–146

Pascal operating system 234

period (.) as Monitor command 102

peripheral address bus 192, 194

peripheral cards

device assignment 145

I/O memory space 133, 141

programming for 132–156

RAM space 136

ROM space 133–135

peripheral data bus 192

differences in Apple II family
231

peripheral slots *See* expansion slots

ø0 (phi 0) 162, 170, 171,
180–181

ø1 (phi 1) 162, 170, 171,
180–181

ø2 (phi 2) 162

phone jacks 8, 39

PINIT subroutine 69

pipelining 161

PLOT subroutine 67, 223

POKE command 271–272

power connector 160

power supply 4, 159–160

PR# command 115

PRBL2 subroutine 67, 224

PRBLNK subroutine 224

PRBYTE subroutine 67, 224

PREAD subroutine 43, 69, 224

PRERR subroutine 67, 224

PRHEX subroutine 68, 224

primary character set 19–20, 228

PRINTER command 115

PRNTAX subroutine 68, 224

ProDOS 105, 141, 233

interrupt support 148–149

starting up with 268

use of page 3 78

use of page zero 81

ProFile hard disk xxii

Programmed Array Logic (PAL)

device 5, 167–168

prompt characters 60

PSTATUS subroutine 71

PWRITE subroutine 69

Q

Q3 signal 163

question mark (?) as prompt
character 62

R

radio-frequency modulator 7

RAM

addressing 139, 169–172

allocation 76–81

auxiliary 86–88

space for peripheral cards 136

timing signals 172

RAMRD soft switch 88–90

RAM upgrade xxiii

RAMWRT soft switch 88–90

random number generator 59

RDALTCHAR soft switch 29

RDALTZP soft switch 84