

SPF - Stress ProDOS Filesystem

The purpose of SPF is simple: to stress-test the ProDOS filesystem to ensure that reads and writes agree, on every byte of the filesystem, every time.

SPF comes on a virtual disk image that can be reconstituted to a physical floppy via ADTPro, or mounted as a virtual floppy disk image on the CFFA3000. The disk is a bootable ProDOS volume, and will start up with a simple menu that lets you either start SPF, or quite to Applesoft BASIC:

```
WELCOME TO STRESS PRODOS FILESYSTEM!  
START THE PROGRAM, OR EXIT TO BASIC?  
(S)TRESS PRODOS FILESYSTEM  
(Q)UIT
```

Pressing the S key on the Apple II keyboard will bring up the main menu of SPF:

```
      S P F F  
      V . F . M  
  
  (L)OW-LEVEL VOLUME CERTIFY  
(V)OLUMES (F)ORMAT (?) (Q)UIT:
```

From the main menu of SPF, you can choose any of several options with the Apple II keyboard:

- L - Perform a low-level certification test of a volume
- V - View the volumes currently online in the system
- F - Format a volume
- ? - See the 'about' text
- Q - Quit to the ProDOS program selector

A quick tour of low-level volume certification follows.

Hitting the L key on the Apple II, you are presented with a list of available volumes to test:

```
CHOOSE VOLUME FOR LOW-LEVEL

SLOT    VOLUMES    CURRENTLY ON-LINE:
-----
3        2        RAM                                127
6        1        SPF.V.R.M                        280

CHANGE SELECTION WITH ARROW KEYS&RETURN
(R) TO RE-SCAN DRIVES, ESC TO CANCEL
```

From the low-level volume selection screen, you can choose a volume to test. Note that testing the 127-block RAM disk does not work; but any other real or emulated volume should. Choosing to test the disk in slot 6, drive 1 would of course overwrite and destroy the contents of the SPF diskette itself - but that's what we'll test with in this demonstration. When making a selection, you are asked twice to verify that you want to proceed. This is important because all data on the selected volume will be irreparably destroyed.

```
CHANGE SELECTION WITH ARROW KEYS&RETURN
READY TO DESTROY UNIT? (Y/N):
```

Once testing commences, data will be repeatedly written and read from the chosen volume. The first pass will write the hexadecimal byte \$AA (10101010 in binary) to every byte in every block of the volume. Once every byte is read back and verified that it matches, the hexadecimal byte \$55 (01010101 in binary) is then written to every byte on the volume, and that is read back and verified too. Once complete, the cycle goes back to \$AA bytes, and so on until stopped with the escape key.

On-screen, there will be status updates from time to time: the number of blocks read so far (only updated every 256 blocks), the total number of blocks in the volume under test, and the number of complete "passes" so far - the number of times the entire volume has been filled with a value and read/confirmed that the value was present in every byte. A typical screen might look like this, with the elements identified above circled in yellow:

```
CHOOSE VOLUME FOR LOW-LEVEL

SLOT   VOLUMES   CURRENTLY ON-LINE:
-----
3      2      RAM      127
6      1      SPF.V.R.M 280

TESTING IN PROGRESS. ESC TO STOP.
READING BLOCK 00256 OF 00280
00004 FULL DISK PASSES COMPLETE
```

If there are problems with ProDOS read or write MLI calls, that will be indicated on the screen. It will identify whether the read or write operation failed, which block it failed on, and the ProDOS MLI error code associated with the failing call:

```
CHOOSE VOLUME FOR LOW-LEVEL

SLOT   VOLUMES   CURRENTLY ON-LINE:
-----
3      2      RAM      127
6      1      SPF.V.R.M 280

TESTING IN PROGRESS. ESC TO STOP.
READING BLOCK 00000 OF 00127
WRITING BLOCK 00003 HAD ERROR CODE: 00
00004 FULL DISK PASSES COMPLETE
```

Similarly, if the validation of a byte fails to compare correctly with what was originally written, the message will indicate that the operation was “VRFYING,” and it will include the failing block as well as the value discovered there when either \$AA or \$55 was expected:

```
CHOOSE VOLUME FOR LOW-LEVEL  
SLOT    VOLUMES CURRENTLY ON-LINE:  
-----  
3        2        RAM                127  
6        1        SPFF.V.R.M         280  
  
TESTING IN PROGRESS. ESC TO STOP.  
READING BLOCK 00000 OF 00127  
VRFYING BLOCK 00003 HAD ERROR CODE: 00  
00004 FULL DISK PASSES COMPLETE
```